

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com



KVM Switch - 32-Port (4-User) 1U Rackmount Cat5 Matrix KVM Switch

MODEL NUMBER: B060-032





Description

Tripp Lite's 32-port NetDirector® 1U Rackmount Matrix KVM Switch is the optimal solution for controlling multiple computers (combination of PS/2, USB, or Sun) by four independent, simultaneous users. A single unit occupies a mere 1U of rack space, yet can control up to 32 computers. A maximum of 2,048 computers can be connected through a combination of daisy-chaining and cascading. RJ45 connections allow signals to travel up to 150 meters away(500ft), using ordinary Cat5 cable, while maintaining video resolution. Use either PS/2 or USB console equipment to connect to PS/2, USB, or SUN Servers. For Government purchasers, B060-032 is Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Three Level password security: Super Administrator, Administrator, and Users
- Superior video quality up to 1024 x 768 @ 60Hz at 500ft.
- Auto Signal Compensation (ASC) assures optimum video resolution for distances up to 500ft between the switch and the consoles or computers - no dip switch setting required
- PS/2 keyboard and mouse emulation computers boot even when the console focus is elsewhere.
 Keep Alive feature ensures that the keyboard and mouse work properly even if the switch temporarily loses power
- Daisy chain up to 7 additional B060-032 KVM Switches
- Cascade up to 32 B060-032 KVM switches from each station on the chain
- Up to 2,048 computers on a daisy chained/cascaded installation
- No software required; convenient computer selection via intuitive hotkey combinations or On Screen Display (OSD) menus
- OSD port list automatically expands when stations are added port names are automatically reconfigured when the station sequence is changed
- OSD screen automatically adjusts to resolution changes

Highlights

- Four consoles independently and simultaneously control up to 32 directly connected computers, or over 2,000 when additional KVM's are connected
- Multi-Platform support: PC, Sun, or Mac
- Rackmountable in a 1U design, with 32 available
 ports...Rackmount Hardware
 Included
- Inexpensive Cat5 cabling makes cable management a breeze;
 500ft distance from Console to switch, or 500ft from Switch to
 Servers
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Console: The Tripp Lite B062-002-PS2 or B062-002-USB
 Console Interface Module must be used to connect a console (Keyboard, Monitor and Mouse) to the KVM switch
- Computers: The Tripp Lite B054-001-SUN, B054-001-PS2 or B054-001-USB Server Interface Module must be used to connect a computer/server to the KVM switch

Package Includes

- 1 B060-032 KVM Switch
- 1 Power Cord
- 1 Daisy Chain Cable





- Hot pluggable; add or remove components without having to power off the switch
- USB & PS/2 Consoles can control any combination of USB, PS/2, or SUN computers
- LCD, VGA, SVGA, XGA, and MultiSync support; DDC2B
- Rackmount Hardware Included
- Lifetime firmware upgrading via flash ROM
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

- 1 CD with Owner's Manual
- 1 set Rackmount Hardware

Specifications

OVERVIEW	
UPC Code	037332123008
Users	4
Console	No
Max CPU	2048
PHYSICAL	
Shipping Dimensions (hwd / in.)	5.500 x 20.000 x 13.000
Shipping Dimensions (hwd / cm)	13.97 x 50.80 x 33.02
Shipping Weight (lbs.)	12.2000
Shipping Weight (kg)	5.53
Color	Black
LCD Monitor (in.)	Not Applicable
LCD Monitor (cm)	Not Applicable
ENVIRONMENTAL	
BTUs	38.9 to 41.7
COMMUNICATIONS	
Port Control	Hotkeys, OSD
IP Remote Access	Yes
CONNECTIONS	
Ports	32
PC/Server Connections	USB; PS/2; VGA

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies